

BOOMER™ CAB  
COMPACT TRACTORS  
37 TO 47 HP

BOOMER™ 37 | BOOMER™ 41 | BOOMER™ 47





## THE TRACTOR YOU NEED WITH THE COMFORT YOU WANT

The BOOMER™ family just got better. Enjoy the convenience and comfort you want without sacrificing the performance and power you need. New Holland Boomer 37, 41, and 47 now come with a factory-installed cab.

- Climate control to keep warm in the winter and cool in the summer
- Side and rear opening windows for natural ventilation for use during less harsh weather
- Comfortable cloth seat with weight control, easy fore / aft movement and adjustable armrests
- Conveniently located controls on the right fender
- Great visibility to the rear drawbar and linkage
- Large 12-gallon / 47-liter fuel tank located under the cab

### THE POWER YOU NEED

Quiet, fuel-efficient engines give you the power you need for loading, mowing, digging, blowing snow, tilling, and much, much more. You get fast implement response and steering thanks to the high-capacity, dual-pump hydraulic system to help you finish any job.



### READY FOR ANY JOB

Whether you need to load mulch, mow the lawn, clear a pasture, dig a trench, till the garden, move snow, clean stalls or install a fence, Boomer tractors are for you. These tractors make it easy to change implements so you can move quickly from job to job.

### SIMPLE OPERATION

Whether you choose the three-range HST (hydrostatic) or SSS (synchronized shuttle shift) transmission, you'll enjoy the ease of operation of the all-new Boomer Cab Series.





The Boomer cab offers superior visibility and comes standard with premium controls that are located conveniently within your reach.

### EASY ACCESS

You always have access to what you need. Whether it is checking the oil, changing the battery, or replacing air filter, the wide-opening hood of the Boomer tractor makes serviceability a breeze.



We've got your back with the FREE Boomer Guard<sup>5</sup> Limited Warranty. It provides five years of worry-free operation, including two years of bumper-to-bumper coverage plus an extra three years of power train protection. You won't find a better compact tractor or warranty anywhere.

FRONT LOADER MODEL		250TLA	260TLA
TRACTOR MODEL		BOOMER™ 37	BOOMER™ 41 BOOMER™ 47
Lift Capacity (500 mm forward, max height)	lbs. (kg)	1,354 (614)	1,849 (839)
Lift Capacity (bucket pivot pin, max height)	lbs. (kg)	1,822 (826)	2,371 (1876)
Breakout force (500 mm forward)	lbs. (kg)	2,444 (1109)	3,191 (1447)
Breakout force (bucket pivot pin)	lbs. (kg)	3,257 (1477)	4,081 (1851)
Max lift height (to bucket pivot pin)	in. (mm)	104 (2642)	109 (2769)
Max dump angle	degrees	48°	56°
Bucket roll back angle	degrees	30°	28°
<b>Cycle times</b>			
Raising time	seconds	3.8	3.8
Lowering time	seconds	2.0	2.0
Bucket dump time	seconds	3.5	3.5
Bucket roll back time	seconds	2.2	2.2

### STANDARD FEATURES:

- Heat and air conditioning
- Interior light
- Front window sunscreen
- 12-volt interior power outlet
- Interior rearview mirror
- 85-amp alternator
- Easy-access exterior filters
- Front wiper and washer
- Front cab roof work lights
- Radio ready – speakers, wiring and external antenna

### OPTIONAL FEATURES:

- Rear work lights (cab roof mounted)
- Rear window wiper and washer
- Safety beacon

# BOOMER™ CAB COMPACT TRACTOR SPECIFICATIONS

MODEL		BOOMER 37	BOOMER 41	BOOMER 47
<b>ENGINE</b>				
Gross horsepower	hp (kW)	36.2 (27)	40.7 (30)	45.6 (34)
Rated speed	rpm	2600	2600	2600
No. of cylinders		3	4	4
Aspiration		Turbo	Natural	Natural
Displacement	cu. in. (L)	92 (1.5)	135 (2.2)	135 (2.2)
Air cleaner		Replaceable dry element	Replaceable dry element	Replaceable dry element
Fuel tank	gal. (L)	12.4 (47)	12.4 (47)	12.4 (47)
Alternator	amps	85	85	85
<b>PTO</b>				
PTO HP (Gear)	hp (kW)	29.6 (22)	32.4 (24)	37.3 (28)
PTO HP (HST)	hp (kW)	28.1 (21)	30.4 (23)	35.0 (26)
PTO speed	rpm	540	540	540
PTO type		Independent with electro-hydraulic engagement		
Mid-PTO Speed		2000	2000	2000
<b>TRANSMISSION</b>				
Type, Mechanical / Hydrostatic		12x12 / HST+3 range	16x16 / HST+3 range	16x16 / HST+3 range
Maximum forward speed,		Manual lever	Manual lever	lever
Gear	mph (kph), R4	14.2 (22.9)	17.0 (27.3)	17.0 (27.3)
HST	mph (kph), R4	14.8 (23.8)	7.9 (28.8)	17.9 (28.8)
Gear/shuttle type		Synchro	Synchro	Synchro
Rear diff. lock engagement		Mechanical	Mechanical	Mechanical
Brake type		Wet, Multi Disc	Wet, Multi Disc	Wet, Multi Disc
<b>HYDRAULICS</b>				
Implement hydraulic flow	gal. (lpm)	8.2 (31.0)	8.2 (31.0)	8.2 (31.0)
Steering hydraulic flow	gal. (lpm)	4.2 (15.9) Gear / 5.3 (19.9) HST		
Mid mount valve		Standard	Standard	Standard
Remote valves		Optional	Optional	Optional
3-point lift capacity @ ball ends	lb. (kg)	1,808 (820)	2,756 (1250)	2,756 (1250)
3-point linkage category		1	1	1
Steering type		Hydrostatic	Hydrostatic	Hydrostatic
<b>DIMENSIONS</b>				
Wheel base	in. (cm)	66 (167.6)	73.2 (186)	73.2 (186)
Length	in. (cm)	119 (302.4)	128.1 (325.4)	128.1 (325.5)
Width	in. (cm)	66.4 (168.7)	69.1 (175.5)	69.1 (175.5)
Height (CAB)	in. (cm)	90 (228.6)	94 (238.76)	95 (238.76)
Weight	lbs. (kg)	3,574 (1622)	4,194 (1903)	4,194 (1903)



We are proud to support the FFA.

Learn more at [www.newholland.com/na](http://www.newholland.com/na)

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 2015 CNH Industrial America LLC. All rights reserved. New Holland is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies, other than owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates, are the property of those respective companies.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

NH36145335 • 121508 • OTP • PRINTED IN U.S.A.