



LAZER Z[®] E-SERIES

**THE DEFINITION
OF VALUE.**

Is the perfect choice for professional landscape contractors who want the innovative engineering and commercial-grade quality of a Lazer Z, but in a value package. Features the same welded, heavy-duty, 1.5"x3" tubular steel unibody frame found throughout our Lazer Z models. A digital operator diagnostic module simplifies system monitoring and troubleshooting, while the fuel gauge uses ultrasonic waves to provide a more accurate reading. In short, the Lazer Z E-Series strikes a perfect balance of value and performance. Now available with Rear Discharge.

FEATURES:

- Choose from Kawasaki[®] or Kohler[®] equipped engines.
- UltraCut™ Series 4 deck with 48/52/60/72-inch cutting widths.
- Heavy-duty canister air filtration system.
- Two Exmark[®] exclusive Parker unitized pump and wheel motor systems with no hoses.
- Ground speeds up to 8.0 mph.




DECK SUPPORT SYSTEM

A cutting deck this good deserves support that's every bit as good. That's why we developed a Panhard rod and strut systems to eliminate side-to-side deck sway. Yes, it reduces wear. And maintenance costs, too.



UNIBODY FRAME

Our one-piece body frame is a great example of "less is more" engineering. Fewer parts equal more strength. And, more durability. So, at least in this case, less is way more.



HYDRO DRIVE SIMPLIFIED

Our innovative hydro-drive system needs only simple, annual maintenance, because it has no hoses to leak and just one easy-to-change belt. As an added bonus, it also lowers the center of gravity for improved handling.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. · 2101 ASHLAND AVENUE · P.O. BOX 808 · BEATRICE, NE 68310-0808 · CALL 402.223.6300 · FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark[®] and Lazer Z[®] are registered trademarks of Exmark Mfg. Co., Inc. ©2016 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2016.

LAZER Z[®] E-SERIES

SPECIFICATIONS

MODEL NUMBER	ENGINE	SIZE	DECK	WEIGHT	LENGTH	HEIGHT	WIDTH DEFL. DOWN	WIDTH DEFL. UP
LZE651GKA484A2	FX651V Kawasaki [®]	48"	UltraCut™ Series 4	1118 lbs	79.2"	70.0"	59.6"	51.8"
LZE730GKA524B2	FX730V Kawasaki	52"	UltraCut Series 4	1185 lbs	79.2"	70.0"	64.8"	56.3"
LZE732GKC524A2	CV732 Kohler [®]	52"	UltraCut Series 4	1120 lbs	79.2"	70.0"	64.8"	56.3"
LZE740EKC60400	ECV740 Kohler EFI	60"	UltraCut Series 4	1115 lbs	83.1"	70.0"	72.8"	62.5"
LZE742GKC604A3	CV742 Kohler	60"	UltraCut Series 4	1151 lbs	83.1"	70.0"	72.8"	62.5"
LZE742GKC604B1	CV742 Kohler	60"	UltraCut Series 4	1316 lbs	83.1"	70.0"	72.8"	62.5"
LZE801GKA604A3	FX801V Kawasaki	60"	UltraCut Series 4	1180 lbs	83.1"	70.0"	72.8"	62.5"
LZE801GKA604B1	FX801V Kawasaki	60"	UltraCut Series 4	1316 lbs	83.1"	70.0"	72.8"	62.5"
LZE801GKA724A3	FX801V Kawasaki	72"	UltraCut Series 4	1243 lbs	86.1"	70.0"	84.9"	73."
LZE801GKA60RA1	FX801V Kawasaki	60"	UltraCut Rear Discharge	1281 lbs	87.2"	70.0"	66.2"	n/a
LZE801GKA72RA1	FX801V Kawasaki	72"	UltraCut Rear Discharge	1326 lbs	87.2"	70.0"	78.2"	n/a

POWER COMPONENTS

Engines – FX651V, FX730V & FX801V Kawasaki[®] V-Twin, CV732 & CV742 Kohler[®] and ECV740 Kohler[®] EFI engines. All engines are governed to 3,750 rpm.

Air Filter – Heavy-duty canister air filtration system.

Drive System – Two Exmark[®] exclusive Parker unitized pump and wheel motor systems with no hoses, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 12cc pumps and 14.5 cubic inch motors. 60" & 72" units also has integrated cooling fans and shock valves.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection 0–8.0 mph (12.9 kmph) forward, 0–6.0 mph (9.7 kmph) reverse on 48" and 52" units. Infinitely variable speed selection from 0–10.0 mph (16 kmph) forward, 0–6.0 mph (9.7 kmph) reverse on 60" and 72" units.

PTO Engagement – MagStop Electromagnetic 175 ft-lbs clutch with spot brake on 48" and 52" models. MagStop electromagnetic 200-ft-lbs clutch with spot brake on 60" and 72" models.

Fuel Capacity – 8-gallon (30.3-L), single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock with safety interlock system indicators.

Rollover Protection System (ROPS) – 2-post foldable ROPS standard with seat belt and latch.

Quick Deck Lift – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

DECKS

Style – Full-floating UltraCut™ Series 4. Side-discharge standard with the option to bag or mulch. Rear-discharge decks have UltraCut™ Rear Discharge cutting deck with option to mulch.

Widths Available – 48" (122 cm), 52" (132 cm), 60" (152 cm) and 72" (183 cm).

Deck Construction – 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt and 7-gauge reinforced spindle mounting locations for improved strength. 4-point suspension, full-floating deck with 3 adjustable anti-scalp rollers on 48" & 52". 4 adjustable anti-scalp rollers on 60"; 6 adjustable anti-scalp rollers on 72". Rear-discharge decks 7-gauge high strength alloy top that is formed and continuously seam welded, with 7-gauge high strength alloy side skirt. 5.5"-deep deck.

Cutting Height – 1.0" (2.5 cm) to 5.5" (11.4 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

Blade Spindles – No maintenance, sealed and non-greasable spindles. 7.75"-diameter cutter housing with 25mm (.98")-diameter spindle shaft and splined blade driver.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

Steering and Motion Control – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampers (3-positions) to customize drive responsiveness. Also adjustable to 2-height positions.

Casters – .50" thick caster yoke arm.

Front Caster Tires – 13 x 5.0-6, smooth-tread, semi-pneumatic. A3 models have 13 x 6.5.0-6, smooth-tread, pneumatic. A1, B1 models have 13 x 6.5.0-6, smooth-tread, semi-pneumatic.

Drive Tires – 23 x 9.5-12, 4-ply Super Turf drive tires on 48" and 52" models. 24 x 12-12, 4-ply Super Turf drive tires on 60" and 72" model.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated disc brake.

Seat – Two-toned, bolstered seat with Elastomeric Vibration Controlled material. Adjustment: fore and aft from operator's position. A1, A2, A3 have deluxe, bolstered suspension seat with Elastomeric Vibration Control material.

Diagnostics – Operational diagnostics with integral fuel gauge.

Electrical – 12-volt battery with 15-amp alternator. 20-amp on Kohler EFI models.

Engine Hour Meter – Standard.

Cup Holder – Standard.

ACCESSORIES & OPTIONS

12-Volt Adapter, Equipment Cover, Extended Drive Lever, Floor Pan Mat, Harness Add-On Accessory Kit, Hitch Kit, Hydro Maintenance Kit, Jack/Receiver, Light Kit, Power Deck Lift, Sun Shade, Trash Container, Air Ride Suspension Seat, Full-Suspension Seat and Tilt Frame & 3D Isolation System Kit. **Side-Discharge Only:** 3-Bushel Bagger, Mulching Kit, Turf Stripper, UltraVac Systems, Weight Kit. **Rear-Discharge Only:** Finish Cut Baffles, Side Wear Bar Kit, White Non-Marking Side Bumper.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark[®] and Lazer Z[®] are registered trademarks of Exmark Mfg. Co., Inc. ©2016 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2016.