



PIONEER® E-SERIES

**BUILT TO LAST.
EQUIPPED TO SAVE.**

The Pioneer E-Series offers lawn care professionals the best of both worlds. On one hand, it has a host of commercial-grade features—like the incredibly smooth, long-lasting ZT2800 hydrostatic drive system, a choice of rugged, Kawasaki® V-Twin engines, a heavy-duty, 2x2" square-tube unibody frame and a patented cutting-deck design for professional results. On the other hand, the E-Series provides tremendous value. Which makes it the ideal mower for anyone who's looking for a great value on a commercial-grade mower.

FEATURES:

- Equipped with a Kawasaki engine.
- UltraCut™ Series 2 deck with 48-, and 52-inch cutting widths.
- Dual Hydro-Gear® ZT2800 hydrostatic transmission with charge pumps.
- Ground speeds up to 7.0 mph.



EVEN FILLING UP IS EFFICIENT

The Pioneer's hefty, 7-gallon fuel tank with a single-fill location means less time pumping gas. And, more time cutting grass.



SAFETY-PLUS

The Pioneer's Rollover Protection System is an important safety feature. Even more its rear-sloping design helps deflect branches away from the operator.



LOCK DOWN

An easy-to-use transport lock conveniently holds the deck up for trailering and enables manual feathering on uneven terrain.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. · 2101 ASHLAND AVENUE · P.O. BOX 808 · BEATRICE, NE 68310-0808 · CALL 402.223.6300 · FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Pioneer® are registered trademarks of Exmark Mfg. Co., Inc. ©2016 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2016.

PIONEER® E-SERIES

SPECIFICATIONS

MODEL NUMBER	ENGINE	SIZE	DECK	WEIGHT	LENGTH	HEIGHT	WIDTH DEFL. DOWN	WIDTH DEFL. UP
PNE651GKA48200	FR651V Kawasaki®	48"	UltraCut™ Series 2	800 lbs	78.0"	71.0"	60.0"	48.2"
PNE691GKA52200	FR691V Kawasaki	52"	UltraCut Series 2	810 lbs	78.0"	71.0"	64.0"	52.8"

POWER COMPONENTS

Engines – FR651V and FR691V Kawasaki® engines; governed to 3,600 rpm.

Air Filter – Standard engine manufacturer's air filter.

Drive System – Dual Hydro-Gear® ZT2800 hydrostatic transmission with charge pumps, no hoses, integrated cooling fans, remote reservoir, spin-on filter and heavy-duty components.

Hydro Fluid – Exmark Premium Hydro oil.

Speed – Infinitely variable speed selection from 0–7.0 mph (11.3 kmph) forward, 0–4.0 mph (6.4 kmph) reverse.

PTO Engagement – MagStop electromagnetic 125-ft-lb clutch.

Fuel Capacity – 7-gallon (26.5-L) single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock with safety interlock system indicators.

Rollover Protection System (ROPS) – 2-post foldable ROPS standard with seat belt and latch.

Deck Lift – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

DECKS

Style – Full-floating, UltraCut™ Series 2. Side-discharge standard with molded discharge chute and the option to bag or mulch.

Widths Available – 48" (122 cm) and 52" (132 cm).

Deck Construction – 10-gauge top that is formed and continuously seam welded and 10-gauge side skirt. 4-point suspension, full-floating deck with 3 adjustable, anti-scalp rollers.

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.25" (.6 cm) increments, adjustable from operator seat.

Blade Spindles – No maintenance, sealed and non-greasable spindles; 7.50"-diameter cutter housing contains 17mm- (.67") diameter spindle shaft and hex blade drive.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Steering and Motion Control – Hydraulically dampened twin levers adjustable both fore and aft. Also has 3-position height adjustment.

Casters – 0.38"-thick caster yoke arms.

Front Caster Tires – 13 x 5.0-6, smooth tread, pneumatic.

Drive Tires – 20 x 8.0-10 Super Turf® drive tires.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated pawl brake.

Seat – Commercial-grade, high-back contoured foam padded with armrests. Hinged mounting with spring suspension. Adjustment is fore and aft from operator's position.

Electrical – 12-volt battery with 15-amp alternator.

Engine Hour Meter – Standard.

Cup Holder – Standard.

ACCESSORIES & OPTIONS

2-Bag Collection System, Equipment Cover, Full-Suspension Seat, Hitch Kit, Jack/Receiver, Light Kit, Mulching Kits, Sun Shade and Trash Container.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Pioneer® are registered trademarks of Exmark Mfg. Co., Inc. ©2016 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2016.