



PIONEER® S-SERIES

**PROOF THAT VALUE
AND PERFORMANCE
ARE NOT MUTUALLY
EXCLUSIVE.**

The Pioneer S-Series gives lawn care professionals even more to like. Take the cutting decks, for example. The 48- and 52-inch models receive the patented UltraCut™ Series 3 deck system. And the 60-inch gets the UltraCut Series 4, the same deck used on our Lazer Z® S-Series mower, featuring heavy-duty cutter housings and a deeper deck for increased productivity. The S-Series also gives you the choice of a ZT3100 (on 48"-52"). The 60" models ZT3400 integrated transmission provide a seriously smooth ride. The S-Series can also reach speeds up to 9 mph on 60" units, which results in maximum productivity.

FEATURES:

- Choose from Kawasaki® or Kohler® equipped engines.
- UltraCut Series 3 deck with 44-, 48-, and 52-inch cutting widths. 60-inch has UltraCut Series 4 or UltraCut Rear-Discharge deck available.
- Heavy-duty canister air filtration system.
- Dual Hydro-Gear® hydrostatic transmission with charge pumps.



REAR-DISCHARGE DECK (60")

The hefty 60" rear-discharge deck allows for increased productivity while mowing around trees, buildings and landscapes. Even more, its controlled discharge helps keep the operator clean.



MAINTENANCE-FREE SPINDLES

Commercial-grade, cast aluminum spindles feature sealed bearings to resist damage from moisture and impact, with no annual greasing required.



COMFORT COUNTS

The Pioneer features a bolstered seat with coil-spring suspension. Not a big deal unless, of course, you're the one sitting in the seat. Then you'll thank us.

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Pioneer® are registered trademarks of Exmark Mfg. Co., Inc. ©2016 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2016.

PIONEER® S-SERIES

SPECIFICATIONS

MODEL NUMBER	ENGINE	SIZE	DECK	WEIGHT	LENGTH	HEIGHT	WIDTH DEFL. DOWN	WIDTH DEFL. UP
PNS710GKC48300	ZT710 Kohler V-Twin	48"	UltraCut Series 3	862 lbs	78.0"	71.3"	60.0"	50.7"
PNS720GKC52300	ZT720 Kohler® V-Twin	52"	UltraCut Series 3	868 lbs	78.0"	71.3"	65.0"	54.2"
PNS730GKA604A3	FX730V Kawasaki	60"	UltraCut Series 4	828 lbs	79.0"	71.3"	73.0"	61.4"
PNS740GKC60400	ZT740 Kohler V-Twin	60"	UltraCut Series 4	948 lbs	79.0"	71.3"	73.0"	61.4"
PNS740GKC604A4	ZT740 Kohler V-Twin	60"	UltraCut Series 4	948 lbs	79.0"	71.3"	73.0"	61.4"
PNS740GKC60RA3	ZT740 Kohler V-Twin	60"	UltraCut Rear Discharge	842 lbs	80.8"	72.0"	66.2"	n/a

POWER COMPONENTS

Engines – FX730V Kawasaki®; ZT710, ZT720 and ZT740 Kohler® V-Twin engines. All engines are governed to 3,750 rpm.

Air Filter – Heavy-duty canister air filtration system on Kawasaki.

Drive System – Dual Hydro-Gear® ZT3100, hydrostatic transmission with charge pumps, no hoses, integrated cooling fans, remote reservoir, spin-on filter and heavy-duty components. 60" model uses dual Hydro Gear ZT3400, hydrostatic transmission with charge pumps, relief valves and spin-on filter.

Hydro Fluid – Exmark Premium Hydro oil.

Speed – Infinitely variable speed selection from 0–8.0 mph (12.9 kmph) forward, 0–5.0 mph (8.0 kmph) reverse on 48"/52" models. Infinitely variable speed selection from 0–9.0 mph (14.5 kmph) forward, 0–6.0 mph (9.7 kmph) reverse on 60" model.

PTO Engagement – MagStop electromagnetic 175-ft-lb clutch on 48"/52" models. MagStop electromagnetic 200-ft-lb clutch with spot brake on 60" unit.

Fuel Capacity – 7-gallon (26.5-L) single fuel tank.

Drive-Wheel Release – Standard - allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock with safety interlock system indicators.

Rollover Protection System (ROPS) – 2-post foldable ROPS standard with seat belt and latch.

Deck Lift – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

DECKS

Style – Full-floating 5.0"-deep UltraCut™ Series 3 on 48" & 52" models. Full-floating 5.5"-deep UltraCut Series 4 on 60" model. All models have side-discharge standard with molded discharge chute and option to bag or mulch. Rear-discharge decks have UltraCut™ Rear Discharge cutting deck with option to mulch.

Widths Available – 48" (122 cm) 52" (132 cm) and 60" (152 cm).

Deck Construction – 10-gauge top that is formed and continuously seam welded and 7-gauge side skirt on all units. 60" model also has 7-gauge spindle mounting, 4-point suspension, full-floating deck with 3 adjustable, anti-scalp rollers on 48" & 52" models. 4 adjustable, anti-scalp rollers on 60" model.

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.25" (0.6 cm) increments adjustable from operator position via foot-operated, deck-lift system.

Blade Spindles – No maintenance, sealed and non-greasable spindles. 7.75"-diameter cutter housing with 25mm- (.98") diameter spindle shaft and splined blade driver.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Unibody, welded, heavy-duty 2" square tubular steel.

Steering and Motion Control – Hydraulically dampened twin levers, adjustable both fore and aft. Levers are also adjustable to 3-height positions.

Casters – .38" thick caster yoke arms. .50" thick caster yoke arms on on A3 models

Front Caster Tires – 13 x 5.0-6, smooth tread, pneumatic. 13 x 6.5-6, smooth tread, pneumatic on A3 models.

Drive Tires – 22 x 9.5-12 Super Turf on 48" & 52" models.
23 x 10.5-12 Super Turf tires on 60" model.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated pawl brake.

Seat – Commercial-grade high-back contoured foam padded with armrests. Hinged mounting with spring suspension. Adjustment is fore and aft from operator's position. A3/A4 models have a deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Adjustment is fore and aft from operator's position.

Electrical – 12-volt battery with 15-amp alternator.

Engine Hour Meter – Standard.

Cup Holder – Standard.

ACCESSORIES & OPTIONS

Equipment Cover, Full-Suspension Seat, Hitch Kit, Jack/Receiver, Light Kit, Sun Shade & Trash Container. **Side-Discharge Only:** Mulching Kits, UltraVac E-Series (2-Bag Powered), 3-Bushel Bagger & Turf Striping Kit. **Rear-Discharge Only:** Finish Cut Baffles, Side Wear Bar Kit, White Non-Marking Side Bumper

The brand landscape professionals purchased 2 to 1.

exmark.com



EXMARK MANUFACTURING COMPANY INC. · 2101 ASHLAND AVENUE · P.O. BOX 808 · BEATRICE, NE 68310-0808 · CALL 402.223.6300 · FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Pioneer® are registered trademarks of Exmark Mfg. Co., Inc. ©2016 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2016.